

LS-Dx4SRA SD/HD/3G SDI Splitter

The LS-Dx4SRA are compact and robust 1x4 SDI rackable Splitters. One RU can support from 1 to 6 splitters.

Compliant with SMPTE259M(SD SDI), SMPTE292M(HD SDI) & SMPTE 424M (3G SDI). The input signal is cleaned and reclocked before being duplicated. A built-in automatic cable equalizer allows links up to 210 meters at 2,97Gb/s, 300 meters at 1,485Gb/s and 550m at 270Mb/s.



New 12G SDI
versions available
SMPTE ST2082

Features :

- Compact and robust up to 3G SDI distribution solutions,
- SD / HD / 3G SDI compliant. 6G SDI / 12G SDI option available on request.
- Extended Reach Adaptive Cable Equalizer
- Built-in Reclocker : detects the data rate and adjusts itself to retime the incoming data to suppress accumulated jitter.
- 110-240 VAC 50/60Hz built-in power supply / World-wide IEC Plug*
- Sizes : 485x120x44mm
- 3 years warranty

Ordering informations :

Single 1x4 Splitter : LS-D14SRA / Dual 1x4 Splitter : LS-D24SRA
Quad 1x4 Splitter : LS-D44SRA / Sextuple 1x4 Splitter : LS-D64SRA

* : DC Power supply available on request.